












Mod.													
	cm	Min	Max	mm	n°	n°	n°	PTO	A	B	C	min	max
<b>TFB/Y 120</b>	120	40	110	685   515 315   885	12	36	4	540 (1000)	100	140	120	560	720
<b>TFB/Y 140</b>	140	50	110	875   525 315   1045	12	36	4	540 (1000)	100	160	120	610	770
<b>TFB/Y 160</b>	160	50	110	875   725 355   1245	14	42	4	540 (1000)	100	180	120	660	840
<b>TFB/Y 180</b>	180	50	110	875   925 355   1445	16	48	4	540 (1000)	100	200	120	700	890
<b>TFB/Y 200</b>	200	50	110	875   1125 355   1645	18	54	4	540 (1000)	100	220	120	740	940
<b>TFB/Y 220</b>	220	60	110	1040   1160 520   1680	20	60	4	540 (1000)	100	240	120	790	990
<b>TFB/Y 250</b>	250	60	110	1040   1460 520   1980	22	66	5	540 (1000)	100	270	120	890	1100

Attacco centrale  
Centre mounted linkage  
Mittiger Anbau  
Attelage axial.

Mod.	
	mm
<b>TFB/Y 160</b>	1046   554 524   1076
<b>TFB/Y 180</b>	1046   754 524   1276
<b>TFB/Y 200</b>	1216   784 694   1306
<b>TFB/Y 220</b>	1326   874 804   1396
<b>TFB/Y 250</b>	1326   974 804   1496